

Model	5200	5200 with TR Attachment	6200	8200
Bale Type & Size	Round up to 6.5 ft			Round up to 6.5 ft Square up to 4 x 4 x 8 ft
Bale Capacity	2	2	6	2
Tub length	80"			
Bunk Feeding Capability	Standard			
Total Ration Grain Tank	N/A	40 bushel side mount	N/A	N/A
X-Rotor	Standard			
Twine Cutter	Standard			
PTO Shaft (1000 RPM)	1000 PTO 1 3/8" 21 Spline 80° Constant Velocity			
Discharge Distance	Up to 60 ft			
Number of Flails (Size)	28 (3/4"x1-1/2")			
Rotor Dia. Extend Tips	27"			
Flail Tip Speed	7000 FPM			
Bale Agitators	2 Hydraulically Driven			
Twine Guard Protection	Rotor/Agitators/Axles			
Feed Rate Adjustment	Multi-position Hoop Grate			
Bale Fork	Adjustable	Adjustable	N/A	Adjustable
Bale Lift Cylinders (Nitrile Shafts)	Dual 3" x 18"			
Hydraulic Lift Deflector Chute	Standard			
Horsepower Required	100-150	100-150	100-150	100-150
Tires	16Lx16.1-6 ply Flotation Tires	16Lx16.1- 6 ply Flotation Tires	14Lx16.1-12 ply Flotation Tires	16Lx16.1-6ply Flotation Tires
Dimensions W x H x L	9' 4"x 8' 9" x15' 7"	10' 5"x8' 9"x15' 7"	9' 4"x8' 9"x38'3"	9' 9" x9' 6"x15' 7"
Weight (Lbs)	4400	5240	9060	4700
Adjustable Hitch	Cast with Optional Clevis Insert			
Safety Chain	Standard			
Road Lights	Standard			
Cylinder Safety Locks	Standard			
Hydraulic Remotes	2 or 3	2, 3 or 4	3 (with control box)	2, 3 or 4
Fine Chop	Optional			
Finish	Powder Coat			
Warranty	2 Year Parts, 1 Year Labour			

Model	GT 40 Pallet Fork	GT 40 3-pt Hitch Attachment	GT 40 Trailer Attachment
Grain Tank Capacity	40 Bushel		
Bunk Feeding Capability	Standard		
Mounting option	Front End Loader	Tractor (Cat. 1 or 2)	Tractor or Truck
Standard Hydraulic Drive	1 Remote Required		
Optional Electric Drive	Onboard 12V Battery with Remote Control and Charger		
Dimension W x H x L	9' x 5' x 3'	9' x 5' x 4'	9' x 7' x 8'
Weight (Lbs)	650	700	860
Tires	-	-	P215/70 R15
Finish	Powder Coat		
Warranty	2 years, 1 years labour		

Model	BR820
Maximum Bale type & size	6.5 ft round
Bale capacity	8 bales - 5ft
Tires	14L x 16.1-12 ply flotation tires
Axles	8000 lb Torflex Axles
Twine guard protection	Conveyor Chain/Axles
Loading	1/4 Turn Bale Arm & Stack Retriever
Dimensions W x H x L	7' 10" x 11' 10" x 45' 10"
Weight (Lbs)	8800
Adjustable Hitch	Cast with Optional Clevis Insert
Safety chain	Standard
Transport light	Standard
Hydraulic Remotes	3
Finish	Powder Coat
Warranty	2 years parts, 1 year labour