

**Bale King Processor Specifications**

Model	5200	5300	5225	6200	8200
Bale Type & Size	Round up to 6.5'				Round up to 6.5' Square up to 4x4x8'
Rate Capacity	2	up to 3	2	6	2
Tub length	80"				
Bunk Feeding Capability	Standard				
Total Ration Grain Tank	40 bu. With TR kit	40 bu. With TR kit	100 bu. Front Mount	40 bu. With TR kit	N/A
X-Rotor	Standard				
Twine Cutter	Available				
PTO Shaft (1000 RPM)	1000 PTO 1 3/8" 21 Spline 80 degrees Constant Velocity (1 3/4" available)				
Discharge Distance	Controllable, Easily Spread to 60 ft. or More				
Number of Flails (Size)	28 (3/4"x 1 1/2")				
Rotor Dia. Extend Tips	27"				
Flair Tip Speed	7000 FPM (80 mph)				
Bale Agitators	2 Hydraulically Driven				
Twine Guard Protection	Rotor/Agitators/Axles				
Feed Rate Adjustment	Multi-Position Grate with New Alternating Short and Long Hoops				
Bale Fork tine spacing	Adjustable	Adjustable	Adjustable	N/A	Adjustable
Bale Lift Cylinders (Nitrile Shafts)	Dual 3" x 18"				
Hydraulic Lift Deflector Chute	Hydraulic lift with hinged rubber flap				
Horsepower Required	100-150				
Tires	16Lx16.1 Flotation Tires	16Lx16.1 Flotation Tires	12Lx16.5 NHS 2-10,000 lbs Torflex	14Lx16.1 Flotation Tires	16Lx16.1 Flotation Tires
Dimensions W x H x L	9'4"x8'9"x15'7"	9'4"x8'9"x15'7"	9'4"x9'4"x16'	9'4"x8'9"x38'3"	9'9"x9'6"x15'7"
Weight (Lbs)	4400 lbs	4500 lbs	7850 lbs	9060 lbs	4700 lbs
Adjustable Hitch	Cast with Available Clevis Insert				
Safety Chain	Standard				
Road Lights	Standard				
Cylinder Safety Locks	Standard				
Hydraulic Remotes	2 or 3	2, 3 or 4	3 (with Control Box)		2, 3 or 4
Fine Chop	Available				
Finish	Powder Coat				
Warranty	2 Years Parts, 1 Year Labour				